



coolenergy

TEMPERATURE RENTAL

Fan Coil Unit

15kW Rental AHU



ABOUT THE AIR HANDLER

Cool Energy's 15kW Fan Coil Unit is a light-weight portable unit capable of offering 2,000m³/hr air flow.

The unit requires a water source to the integral coil and has quick release water connections, together with a 13 amp single phase standard power connection.

The fan coil is sited internally and has an adjustable air discharge grill with louvres. The unit is also supplied with an integral condensate pump.

Cool Energy Service

Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW – 1,000kW units.
- Water-cooled rental chiller range from 7.5kW – 1,000kW units.
- Air handling units & fan coils from 5kW – 500kW duties.
- Air conditioning units from 1.3kW – 350kW units.
- Low temperature chillers (-30oC) and fan coils (0oC air off).
- Dehumidifiers (desiccant & electric) 200-10,000m³/hr.
- Generator Power with 20KVA – 800KVA fuel tanks and management.
- Air distribution (flexible ducting and perforated air socks).
- Hot water generators and boilers from 25kW – 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.



TECHNICAL

15kW Comfort Fan Coil (for heating and air conditioning)

Performance data @ design conditions

Cooling Capacity	kW	15
Sensible Cooling Capacity	kW	10
Air Off Temperature	°C	20
Air On Temperature	°C	25

Cooling Operating limits

Min/Max Duty	kW	10/30
Min/Max Air Off Temperature	°C	15/30
Fluid Pressure Drop	kPa	40
Max Working Pressure	kPa	300
Evaporator Water Volume	l	10
Condensate Connection (hose tail)	mm/inches	25/ ½

Air Limits

Total Number Fans	0.4kW each	1
Total Airflow	m ³ /hr	2,000
	m ³ /s	0.56
Max Air Throw	m	8

Electrical data

Electrical Supply Voltage 1 phase	V	240
Power Connections	A	16 C forme plug or 13 amp std
Max Power Absorbed	kW	1.2
Max Current Absorbed	A	5
Starting Current (Max)	A	9
Recommended Generator Set	kVA	N/A
Control System (motorised 3 way valve)	switch	On/Off

Sound Data

Sound Pressure Level at 1 metre (ISO3744)	dB(A)	56
---	-------	----

Physical Data

Overall Length	mm	605
Overall Width	mm	380
Overall Height	mm	1,900
Weight Dry	kg	100
Weight + Water/Glycol mix	kg	110
Fluid Coupling Size	mm/inch	25/1
Fluid Coupling Type	Std	1" Camlock



Head Office South

ICS House, Stephenson Road, Calmore Industrial Estate, Totton, SO40 3RY
T (+44) 23 8052 7300 F (+44) 23 8042 8366

Midlands

Unit 82 Plume Industrial Estate, Holburn Hill, Aston, Birmingham B6 7RT
T (+44) 121 326 7771 F (+44) 121 327 4114

North

Floor 2, Caspian House, East Parade, Little Germany, Bradford BD1 5EP
T (+44) 1274 740 877 F (+44) 1274 391 708

Scotland

Unit 5, 53/58 South Avenue, Blantyre Industrial Estate, Blantyre, G72 0XB
T (+44) 1698 723308 F (+44) 1698 723309

Ireland

Unit 2, Kells Enterprise Centre, Cavan Road, Kells, County Meath, Ireland
T (+353) 46 925 2934 F (+353) 46 925 2936

We also have four locations in Germany in Munich, Guglingen, Hagen and Leipzig. Further information on these locations can be found at www.coolenergy.de



coolenergy

TEMPERATURE RENTAL

www.coolenergy.co.uk

Equipment designed to ISO-9001 and all relevant directives. Product improvement is a continual process at Cool Energy and we reserve the right to change the design and specifications without notice or obligation. Availability is subject to change without notice. Contact your local Cool Energy depot for availability. © 2010 Cool Energy. All rights reserved.