



Anti-slip material for extra safety



Safety light is always lit



Internal lighting safety lights and lamp with sensor



Internal halogen light with sensor, distress alarm and pressure valve



External light with sensor, including alarm, siren, thermometer & pressure valve

Dimensions	Ext.	Int.	Door
Length	12.192	11.200	
Width	2.438	2.294	1.250
Height	2.600	2.280	1,990

Cool Energy's Arctic Store Container type unit – is Ideal for chilling or deep frozen storage applications providing a budget option from 1 week to long-term hire

• **Temperature Range**

The temperature range of these units is -25 °C to +25 °C. Power requirements for the refrigeration system is 415v, 3 phase 32 amp motor rated power supply. The cooling system is specially designed unit giving economy of operation with maximum cooling efficiency.

• **Unit Build Quality**

The range features, Stainless steel or one-piece GRP internal panels. Lighting Rub rails High Strength, hard wearing non-slip resin or chequer plate floor. Externally, the units have smooth aluminium, light grey side panels and white roof giving good levels of heat reflection. The units are suited for indoor or outside use.

• **Health and Safety**

The units have flat floor allowing for easy cleaning limiting bacteria risks. The floor is a high strength flat resin or chequer plate floor permitting the use of forklift or wheeled pallet trollies. The units feature mantrapped alarms and a mains isolator, the units have double doors for easy access with lock and internal safety release, door retainers, plastic strip curtains and heater tapes.

• **Instrumentation and Control**

On/Off switch, temperature display, power on and defrost lights. Electronic data logger monitors cold store and return air temperature, door opening, defrosts and high/low temperature alarms. Alternatively, chart recorder gives a permanent 7 or 31 days temperature record.

• **Transportation and Handling**

The steel base frame design incorporates a unique self loading and unloading transportation system, minimising the time on site to as little as 20 minutes in most cases. No need for jacking legs or cranes, providing site access is suitable.

• **Options and Service**

A range of options are available including personnel and side doors, shelving, racking, multi-compartment partitions, elevation platform, ramps, dock seals, buffers and additional security bars. As standard with your rental agreement service and maintenance is included on a 24/7 basis, with regular scheduled services carried out on site.