

Cool Energy's Climastore Range provides additional storage or warehousing space fast, offering a solution for all budgets and requirements.

Our buildings can be temperature controlled to a wide range including the maintenance of chilled temperatures (**below 4 °C**) and warm storage to help provide the correct control for your products or personnel.

We can provide you or your clients with a temporary unit on a flexible basis to suit your production demands, seasonal turnover and short term emergency projects.

Cool Energy stores are provided in a variety of footprints and height options to help match your sites' bespoke requirements.



- **Building Size Options**
 - Width in multiples of 5m sections
 - Length in multiples of 5m sections
 - Height up to roof slope (eaves) in 3.2m, 4.2m and 4.6m
- **Flexibility**

The Climastore can be built on site to match the vacant space available - there are a wide range of sizes to help meet specific site requirements.
- **Efficiency**

Maximise on-site operations by utilising all your vacant space before committing to costly planning permission for new builds and capital expenditure.
- **Technical features**
 - **Industrial rigid aluminium frame** - with a 10 year guarantee.
 - **PVC polyester roof membrane** - with optional Kingspan.
 - **Access doors** - a choice of roller shutter and rapid release (1meter/second) doors.
 - **Racking** - to match your specific requirements up to 4 pallet height.
 - **Cooling** - low energy use equipment capable of managing 0°C-25°C ambient environments with auto-defrost and temperature measurement/recording.
 - **Heating** - indirect and air conditioned heat to 40°C with internal ducting for air distribution/air handling units.
 - **Guttering** - to suit your site requirements and sited, at the Climastore eaves to localised on-site drainage.
 - **Foundations** - the Climastore can be easily affixed to most sites including tarmac, concrete and hardcore.

- **Safety**

All buildings fully comply with British and EEC safety standard for structural integrity, fire and safety codes including General Snow Loading BS part 3 1988 and General wide Loading CP3 - Chapter V:PT2: 1972.
- **Additional features and Options**
 - A choice of roller shutter or rapid-release (1m/sec) doors.
 - Racking up to 4 Pallet height to match your specific storage requirements.
 - Temperature monitoring with alarms and measurement.
 - Guttering to suit your drainage on site.
 - Fully washable external and internal surfaces.
 - Building can be easily affixed to most sites including tarmac, concrete and hardcore.
 - Availability: the majority of our equipment is ex-stock and can be installed within 14 days.
 - Lighting to suit your site with Hi-Lux supplied as standard with guard.
 - Docking areas can be build and pallet/scissor lifts to assist with movement.
- **Security**

Retain full control over your building of sensitive or high value goods rather than out-sourcing your storage and distribution.
- **Availability**

The majority of our equipment is ex-stock and can be installed and ready for use within 14 days.