

Cool Energy HVAC & Process Fluid Pump Range

Cool Energy's range of fluid pumps are used in conjunction with their rental chillers, air handlers, tanks, heat exchanger and flexible water hoses to provide a reliable flow rate of fluid designed to achieve the required duty.

The final fluid regulation can be managed by the outlet valve on the rental chillers and equipment.



High Pressure Range

Suitable for Chiller	High Pressure	TAE161	TAE351	TAE602	HERCULES	PHOENIX	FOCS3602
					ARIES	FOCS1902	FOCS4222
Pump Model	Lowara	CA200/35	FHE32-200/40	FHE40-200/75	FHS 50-250/150	FHS 65-250/220	FHS 80-250/450
Design Flow	l/s	3.2	7	12	19	29	50
	l/s Max	3.5	8.3	13.3	23	38.9	58.3
	l/s Min	2.8	4.7	8.3	16.6	22.2	41.6
	m3/hr Max	12.5	30	48	83	140	210
	m3/hr Min	10	17	30	60	80	150
Design Pressure	Bar	4.2	4.5	4	5	5	6.2
	Bar Max	4.4	3.5	4.2	5.6	5.6	7
	Bar Min	3.6	1.5	2.2	4.2	3.6	5
Water Connections	Bauer/Flange	2	2	2	4	4	4
Power Connection	Cforme 5 pin Plug	16	16	16	16	32	32
Max Current	A	5.3					
Absorbed Power	kW	2.2	4	7.5	15	22	45
	HP	3	5.5	10	20	30	61
Physical Data	Skid						
	Length mm	1200	1200	1200	1200	1200	1200
	Width mm	400	400	400	460	460	460
	Height mm	650	650	650	1300	1300	1300
	Weight kg	100	125	150	500	600	600
	Sound 1m dB(A)	<70	<70	<70	<70	<70	<70



coolenergy
TEMPERATURE RENTAL

Call now on freephone 0800 840 4210
www.coolenergy.co.uk